



## KX-TVA50

Voice processing System, up to 6 ports, up to 8 hours voice storage

[See Dealer for Price](#)

Buy this product at a store...

[technical specs](#)

[support & resources](#)

		models with this feature
Line Capacity (ports)	2, expandable to 6	
Voice Storage	up to 4 hours, expandable up to 8 hours	
Automated Attendant Service	Yes	
Call Screening	Yes	
Live Call Screening	Yes	
Remote Live Call Screening (DPITS only)	Yes	
Callback Number Entry	Yes	
Caller ID Name Announcement	Yes	
Caller ID Personal Greeting	Yes	

Caller ID Call Routing	Yes
Covering Extension	Yes
Custom Service	Yes
Direct Mailbox Access	Yes, DPITS and APIT only
Email Integration	Yes
Enhanced Message Notification	Yes
External Message Delivery	Yes
Fax Detection	Yes
Holiday Service	Yes
Intercom Paging	Yes, DPITS and APIT only
Interview Service	Yes
Voice Mail Service	Yes
Dialing Method	DTMF
Flash Time	100/300/600/900 msec (programmable)
CPC Detection	None/6.5/150/300/450/600 msec (programmable)
Type of Line	Loop start
Extension Numbering	2-5 digits (programmable)
Pause Time	100ms to 9900ms
Message Waiting Lamp	Yes
Main CPU	32-bit microprocessor
System Recording Time	up to 4 hours (expandable to 8)
Number of Mailboxes	Max. 64 boxes
Number of Messages	unlimited
Personal Greeting Message Length	up to 360 sec.
System Message Retention Time	1-30 Days, or unlimited (programmable)
Maximum Message Length	1-60 min. (programmable)

Telephone Line	Modular connector (RJ-11C) (2 conductor wire)
Data Port	USB, LAN or Modem
Power Source	AC 120V, 60 Hz
Two-Way Record	Yes, DPITS and APIT only
Two-Way Transfer	Yes, DPITS and APIT only
Automatic Configuration	Yes, DPITS and APIT only
Dial by Name	Yes
Group Delivery	Yes
Message Transfer (with or without comments)	Yes
Day/Night Service	Yes
Voice Prompts	Yes
System Reports	Yes
Multilingual Service	Yes
Remote Call Forwarding Set <sup>3</sup>	Yes
Activity Reports	Mailbox Information, Call Account, Port Usage HDD Usage, Mailbox Usage, Fax Call Call Handling Statistics, Custom Service, Message Status Subscriber Setup, Security Information, Hourly Statistics and Email
Greeting, After Hours	Yes
Greeting, Busy	Yes
Greeting, No Answer	Yes
Internal Message Delivery	Yes
Mailbox Name	Yes
Mailbox Password	Yes
Message Delivery Status	Yes
Message Reception Mode	Yes
Message Erase	Yes

Message Fast Forward	Yes	
Message Pause	Yes	
Message Playback	Yes	
Message Repeat	Yes	
Message Rewind	Yes	
Message Save	Yes	
Message Scan	Yes	
Message Skip	Yes	
New Message Notification	Yes	
Play Previous Message	Yes	
Private Messages	Yes	
Reply to Subscriber(s)	Yes	
Time and Date Stamp	Yes	
All Calls Transferred to Mailbox	Yes	
Alternate Extension Transfer Sequence	Yes	
Auto Message Move/ Copy	Yes	
Broadcast Message	Yes	
Call Blocking	Yes	
Call Transfer Status	Yes	
Class Of Service	Yes	
Clock Synchronization with PBX	Yes	
Coverage Mode, Busy	Yes	
Coverage Mode, No Answer	Yes	
Daylight Saving Time Assignment	Yes	
Department Dialing	Yes	

External Message Delivery Status	Yes	
Fax Management	Yes	
Fax Transfer	Yes	
Group Distribution Lists, Personal	Yes	
System Groups Mailbox	Yes	
Hold Call	Yes	
Mailbox, General Delivery	Yes	
Mailbox, Guest	Yes	
Mailbox, Interview	Yes	
Mailbox, Message Manager	Yes	
Mailbox, Subscriber	Yes	
Mailbox, System Manager	Yes	
Message Waiting Notification, Continuous	Yes	
Message Waiting Notification, Outdial	Yes	
Message Waiting Notification, Pager	Yes	
Message Waiting Notification, Scheduled	Yes	
Multiple Company Greetings	Yes	
Operator Service, Day/ Night	Yes	
Recordable System Prompts	Yes	
Rotary Telephone Service	Yes	
Service Access Commands	Yes	
System Clock	Yes	
System Prompts After Personal Greeting	Yes	

Unlimited Message Length	Yes	
Digital Integration	Yes	
In-band Integration	Yes	
PC-based Programming	Yes	
Quick Set-up	Yes	
System Manager Administration	Yes	
Utility Commands	Yes	
Voice Mail Menu	Yes, with KX-TDA with LCD proprietary telephone only	
Remote Change of Company Greeting	Yes	
Built-In Modem for Remote Maintenance	Yes, optional	
Spanish Prompts	Yes	
Dimensions (H x W x D)	7.87" x 14.57" x 12.21"	
Weight	6.91 lbs	