



Toll-Free: (800) 323-9355

Wiring The World

Fax: (847) 689-1192

PRODUCT DATA SHEET

PART NUMBER: 96204
DESCRIPTION: 24 AWG /4 Pair RISER CATEGORY 3 DATA CABLE *Com-Lan 3*
RATING: UL DUAL LISTED CMR and C(UL) CMG FT4 and CMX-OUTDOOR
CERTIFICATIONS: UL Classified Category 3
 ETL Verified Category 3

Construction Parameters:

	<u>INFORMATION</u>	<u>DIAMETER*</u>
Conductors:	Solid Copper	0.020
Dielectric:	Solid SRPVC	0.035
Pair lays:	Each pair has different lay length for cross-talk prevention	-
Ripcord:	Polyester	-
Jacket:	PVC	0.180

Electrical Properties:

DC Resistance Max.(ohms/m @ 20° C):	9.38
DC Resistance Unbalance Max.(%):	5
Characteristic Impedance (ohms): 1-16 MHz	85-115
Pair-to-Ground Cap. Unbal. Max.(pF/100m):	330
Worst-Pair Near-End	772 kHz 43**
Crosstalk Min. (dB):	1.0 MHz 41**
	4.0 MHz 32**
	8.0 MHz 27**
	10.0 MHz 26**
	16.0 MHz 23**

The (**) values are for information only. The min. NEXT coupling loss for any pair combination at room temp. is to be greater than the value determined using the formula $NEXT(F_{MHz}) \geq NEXT(0.772) - 15 \log_{10}(F_{MHz}/0.772)$ for all freq. in the range of 772 Mhz-16 MHz for a min. length of 100 m.

Attenuation Max.(db/100m):	256 kHz	1.3
	512 kHz	1.8
	772 kHz	2.2*
	1.0 MHz	2.6*
	4.0 MHz	5.6*
	8.0 MHz	8.5*
	10.0 MHz	9.7*
	16.0 MHz	13.1*

The asterisk (*) vlues are for information only. The maximum loss for any pair at room temp. is to be determined using the formula $Att(f) \leq 2.32[SQR(f)] + 0.238(f)$

Structural Return	1.0- 10.0 MHz	12
Loss Min. (dB):	16.0 MHz	10**

The (**) values are for information only. The SRL is to be determined using the formula $SRL_F \geq SRL_{10} - 10 \log_{10}(F/10)$

Miscellaneous Information:

Pair Colors: W/BI with BI/W, W/Or with Or/W, W/Gn with Gn/W, W/Br with Br/W
 Jacket Color: Typical is Gray or Beige (others available)
 Jacket Print: CAT3 COLEMAN CABLE E118963T 24 AWG TYPE CMR VERIFIED (UL)
 CAT3 CMX-OUTDOOR C(UL) FT4 (ETL) VERIFIED TO CAT3
 CAT3 CAT3
 (Also printed with sequential footage, date code and reel #)
 Flame rating: UL-1666 Vertical Shaft Flame Test
 Applicable NEC Article: 800
 Voltage Rating: 300V Per NEC Article 800
 Applicable TIA/EIA: 568-A
 Approximate Weight (lb/1000 ft): 18

On special orders the customer will accept all factory lengths and ± 10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We reserve the right to review and modify all constructions to conform with the latest Regulatory requirement. We disclaim all liability in connection with the use of information contained herein or otherwise. This specification is propriety intellectual property of COLEMAN CABLE. Any information contained herein shall not be disclosed to any party without written consent of COLEMAN CABLE.

Company Name: _____

Customer Approval: _____

Date: _____

Issued: 07/9/03

* = Nominal value
 By: PEP

© 2003 Coleman Cable, Inc.